

AVALTA

GRANITO

A STUNNING CRAFTED
DETAILS GIVE GRANDEUR LOOK

600
X1200MM

CARVING
SERIES



IT'S ALL ABOUT US

Avalta is a Group Venture by Avalta Granito which is renowned brands of the ceramic industry, bringing together the best of expertise and experience of more than six years, Avalta aims to revolutionize the industry by introducing never-before seen tiles that are sure to raise the bar of grandeur a notch higher.

Exclusivity in design and exquisite finishes defines the Avalta as Best products offerings. Use of quality certified raw materials and innovative - modern technology, Tiles produces in Avalta are the best blend of stylish designs and productive long lasting strength. With the newfangled ideas, we assure and able to create consolidation of Beauty, Style & Quality in Vitrified Tiles which will drive you to the luxuries way...

MISSION

Willingness towards the enhancement of life style and passionately strive to delight every customer of AVALTA by providing innovative and quality products and services as ongoing basis and to become a most sought after brand.

VISION

Avalta Granito Pvt Ltd is committed to providing technologically-advanced, aesthetically designed, high-strength, premium quality vitrified tiles that satisfy commercial as well residential customer needs in domestic and international markets.

AVALTA
GRANITO



AVALTA
GRANITO

CARVING
SERIES

SIZE

600x1200mm

FINISH

CARVING

The carving effect provides a depth effect to your flooring but also adds a shining effect. The carving effect holds the essence of nature with natural stone design and gives a positive outlook to your space.





ANCO ALMOND



ANCO ALMOND

**600X
1200MM**

**FINISH
CARVING**

**RANDOM
04**



**IMPACT
RESISTANCE**



**HIGH
STRENGTH**



**LOW WATER
ABSORPTION**



**ZERO
MAINTENANCE**





ANCO CREMA



ANCO CREMA


**600X
1200MM**

**FINISH
CARVING**

**RANDOM
03**



**IMPACT
RESISTANCE**



**HIGH
STRENGTH**



**LOW WATER
ABSORPTION**



**ZERO
MAINTENANCE**







ANCO GREY


**600X
1200MM**

**FINISH
CARVING**

**RANDOM
03**



**IMPACT
RESISTANCE**



**HIGH
STRENGTH**



**LOW WATER
ABSORPTION**



**ZERO
MAINTENANCE**





ANCO SILVER



ANCO SILVER

**600X
1200MM**

**FINISH
CARVING**

**RANDOM
03**



**IMPACT
RESISTANCE**



**HIGH
STRENGTH**



**LOW WATER
ABSORPTION**



**ZERO
MAINTENANCE**





BUTED NATURAL



BUTED NATURAL

**600X
1200MM**

**FINISH
CARVING**

**RANDOM
03**



**IMPACT
RESISTANCE**



**HIGH
STRENGTH**



**LOW WATER
ABSORPTION**



**ZERO
MAINTENANCE**






CATAGE MULTI



CATAGE MULTI

**600X
1200MM**

**FINISH
CARVING**



**IMPACT
RESISTANCE**




**HIGH
STRENGTH**



**LOW WATER
ABSORPTION**



**ZERO
MAINTENANCE**







DIA MARBLE

**600X
1200MM**

**FINISH
CARVING**

**RANDOM
02**



**IMPACT
RESISTANCE**



**HIGH
STRENGTH**



**LOW WATER
ABSORPTION**



**ZERO
MAINTENANCE**





HEETS BLACK




HEETS BLACK


**600X
1200MM**

**FINISH
CARVING**

**RANDOM
03**



**IMPACT
RESISTANCE**




**HIGH
STRENGTH**



**LOW WATER
ABSORPTION**



**ZERO
MAINTENANCE**





MATION WHITE




MATION WHITE

**600X
1200MM**

**FINISH
CARVING**

**RANDOM
03**



**IMPACT
RESISTANCE**



**HIGH
STRENGTH**



**LOW WATER
ABSORPTION**



**ZERO
MAINTENANCE**






MENT BEIGE




MENT BEIGE

**600X
1200MM**

**FINISH
CARVING**



**IMPACT
RESISTANCE**




**HIGH
STRENGTH**



**LOW WATER
ABSORPTION**



**ZERO
MAINTENANCE**





PORT NATURAL



PORT NATURAL

**600X
1200MM**

**FINISH
CARVING**

**RANDOM
05**



**IMPACT
RESISTANCE**



**HIGH
STRENGTH**



**LOW WATER
ABSORPTION**




**ZERO
MAINTENANCE**






PRO WHITE




PRO WHITE

600X
1200MM

FINISH
CARVING



IMPACT
RESISTANCE



HIGH
STRENGTH



LOW WATER
ABSORPTION



ZERO
MAINTENANCE




RAGE BROWN



RAGE BROWN

**600X
1200MM**

**FINISH
CARVING**



**IMPACT
RESISTANCE**




**HIGH
STRENGTH**



**LOW WATER
ABSORPTION**



**ZERO
MAINTENANCE**






RAGE GREY



RAGE GREY

**600X
1200MM**

**FINISH
CARVING**



**IMPACT
RESISTANCE**




**HIGH
STRENGTH**



**LOW WATER
ABSORPTION**



**ZERO
MAINTENANCE**





REC CREMA



REC CREMA

**600X
1200MM**

**FINISH
CARVING**

**RANDOM
03**



**IMPACT
RESISTANCE**



**HIGH
STRENGTH**



**LOW WATER
ABSORPTION**




**ZERO
MAINTENANCE**






REDANO GREY



REDANO GREY

**600X
1200MM**

**FINISH
CARVING**



**IMPACT
RESISTANCE**



**HIGH
STRENGTH**



**LOW WATER
ABSORPTION**




**ZERO
MAINTENANCE**






REDANO WHITE



REDANO WHITE

**600X
1200MM**

**FINISH
CARVING**



IMPACT
RESISTANCE



HIGH
STRENGTH




LOW WATER
ABSORPTION



ZERO
MAINTENANCE




SIDING WHITE




SIDING WHITE

**600X
1200MM**

**FINISH
CARVING**



**IMPACT
RESISTANCE**



**HIGH
STRENGTH**



**LOW WATER
ABSORPTION**



**ZERO
MAINTENANCE**



THICK WHITE



THICK WHITE

**600X
1200MM**

**FINISH
CARVING**

**RANDOM
05**



**IMPACT
RESISTANCE**



**HIGH
STRENGTH**



**LOW WATER
ABSORPTION**



**ZERO
MAINTENANCE**





WOOD NATURAL BEIGE




WOOD NATURAL BEIGE

**600X
1200MM**

**FINISH
CARVING**



**IMPACT
RESISTANCE**



**HIGH
STRENGTH**



**LOW WATER
ABSORPTION**



**ZERO
MAINTENANCE**





WOOD NATURAL BROWN



WOOD NATURAL BROWN

**600X
1200MM**

**FINISH
CARVING**



**IMPACT
RESISTANCE**



**HIGH
STRENGTH**



**LOW WATER
ABSORPTION**



**ZERO
MAINTENANCE**



Technical Specifications.

CHARACTERISTIC	STANDARD AS PER ISO-13006/EN 14411 GROUP BIa	MEAN VALUE OF POLISHED GVT	MEAN VALUE OF GVT / PGVT	TEST METHOD
REGULATORY PROPERTIES				
Deviation in length & width	±0.5 %	±0.1 %	±0.1 %	ISO-10545-2
Deviation in thickness	±5.0 %	±4.0 %	±4.0 %	ISO-10545-2
Straightness in side	±0.5 %	±0.1 %	±0.1 %	ISO-10545-2
Rectangularity	±0.5 %	±0.1 %	±0.1 %	ISO-10545-2
Surface flatness	±0.5 %	±0.2 %	±0.2 %	ISO-10545-2
Color dierence	Unaltered	No change	No change	ISO-10545-16
Glossiness	As per mfg	Min 90%	Min 4%	GLOSSOMETER
STRUCTURAL PROPERTIES				
Water absorption	< 0.50 %	< 0.20 %	< 0.20 %	ISO-10545-3
Apparent density	> 2.0 g/cc	>2.10 g/cc	>2.10 g/cc	DIN 51082
MASSIVE MECHANICAL PROPERTIES				
Modulus Of Rupture	Min. 35 N/mm²	Min. 40 N/mm²	Min. 40 N/mm²	ISO-10545-4
Breaking strength	Min. 1300 N	Min. 2000 N	Min. 2000 N	ISO-10545-4
Impact resistance	As per mfg	Min. 0.55	Min. 0.55	ISO-10545-5
SURFACE MECHANICAL PROPERTIES				
Surface abrasion resistance	As per mfg	Min. Class-3	Min. Class-4	ISO-10545-7
MOH's hardness	As per mfg	Min. 4	Min. 5	EN 101
THERMO HYDROMETRIC PROPERTIES				
Frost resistance	No damage	No damage	No damage	ISO-10545-12
Thermal shock resistance	No damage	No damage	No damage	ISO-10545-9
Moisture expansion	Nil	Nil	Nil	ISO-10545-10
Thermal expansion(COE)	Max. 9.0 x 10 ⁻⁶	Max. 6.5x10 ⁻⁶	Max. 6.5 x 10 ⁻⁶	ISO-10545-8
Crazing resistance	As per mfg.	Min. 10 Cycle	Min. 10 Cycle	ISO-10545-11
CHEMICAL PROPERTIES				
Chemical resistance	No damage	No damage	No damage	ISO-10545-13
Stain resistance	Resistant	Resistant	Resistant	ISO-10545-14
SAFETY PROPERTIES				
Slip resistance	As per mfg.	>0.40	>0.40	ISO-10545-17
Fire resistance	As per mfg.	Fire proof	Fire proof	N. A.
Lead & Cadmium given o by glazed tiles	As per mfg.	Does not yield Pb & Cd	Does not yield Pb & Cd	ISO-10545-15

Packing Details.

SR. NO.	PRODUCT	NOMINAL SIZE	TILES PER BOX	COVERAGE AREA
1	VITRIFIED TILES	600 x 1200 mm	2	1.44 Sq. Mtr.

Note: •Colour Shown are as accurate as the limitations of the printing process will allow. •Prospective customers are advised to inspect a sample of the tile before ordering. •Every effort has been made to ensure the accuracy of the information given. •However, the company reserve the right to change the specifications without prior notice. •Sometime variations in shade or size being inherent to ceramic industry may occur. •Before fixing, we advise you to follow the fixing instructions on the cartons of the tiles as no responsibility can be accepted by the company once the tiles have been fixed.





AVALTA GRANITO PVT. LTD.

Customer Care - +91 7211 111 591
Survey No 159, At Ratavirda, Sartanpar Road, Wankaner,
Morbi, Gujarat - 363621, India.

info@avaltagranito.com | www.avaltagranito.com